



Cemtec NA riding shoes

The NA riding shoe has been developed and is being produced especially for the US-market.

Specification

Material	Steel
Clips	Placed on the outside
Nailholes	8 nail holes punched to fit City head nails
Nailcrease	Yes
Worked edges	Yes, inside edge and sole relief
Studholes	None
Winding studholes	-
Finish	The horseshoes are hand polished after production to improve the finish for a more pleasant handling.
Sizing system	American

Packaging

Outside packaging	Rigid carton
Inside packaging	Plastic bag, anticorrosion paper, shock/noise absorbing material
Labelling	4 side colour coded for each type of horseshoe
Pieces / carton	30

Customization


Anything is possible in regards to stud holes, winding, welding reinforcements, packaging etc.

Dimension & Sizes

Size	Length	Width	Breadth	Thickn	Dim.	Clips
Front						
4	112,5	108,6	18	8	18x8	None or quarter
5	118,4	114,3	19	8	19x8	"
6	124,6	120,4	20	8	20x8	"
7	131	126,7	20	8	20x8	"
8	137,7	133	22	8	22x8	"
9	144,6	139,7	23	8	23x8	"
10	151,8	146,5	24	8	24x8	"
11	159,4	154	25,5	8	25,5x8	"
12	165,7	161,7	26,5	8	26,5x8	"
Hind						
4	110,2	109,3	18	8	18x8	None, side or quarter
5	115,7	114,8	19	8	19x8	"
6	121	119,8	20	8	20x8	"
7	128,5	127,2	20	8	20x8	"
8	135	133,9	22	8	22x8	"
9	141,7	140,6	23	8	23x8	"
10	148,8	147,6	24	8	24x8	"
11	156,2	154,7	25,5	8	25,5x8	"
12	164	162,7	26,5	8	26,5x8	"



Measures



Studholes 0



Clips placement

